



# LINEARIS<sup>LC</sup>



Linearis  
Linearis MINI  
Linearis LE  
Linearis LC  
Linearis RM

LINEARIS LC is the desktop version of the LINEARIS series. Almost all of the features available in the high performance RM version are also available in this compact version provided with a maximum of 800 GB of storage.

16 unsynchronized cameras with 8 audio input can be connected to each LINEARIS LC unit, that can be used either as a standalone product or as a server, on any TCP/IP network without loss of performance.

## LINEARIS

LINEARIS is CIEFFE's new Digital Video Management System, a fully automated MPEG4 main profile system capable of reacting to external conditions without user intervention. Available in a new configuration with 6, 12 or 16 input version, LINEARIS seamlessly combines various recording modes with internal motion detection features, fast search capabilities, external alarm inputs and built in relay outputs.

Its flexible architecture and proprietary MPEG4 Main Profile compression algorithm consistently deliver superior visual quality at exceptionally low file sizes. Recording time is thus dramatically increased while costs are significantly reduced.

LINEARIS LC is a Digital Video Management System with an excellent cost-performance ratio and a superior video quality guaranteed by the new generation of DSPs. It's the ideal solution for banks, retail stores, schools, parking lots, and real estates subject to burglary and vandalism.

LINEARIS is a mid-level solution, ideal for multi-site installations where high performance and reliability are required, together with exceptional video quality and high image rates.

The on-board DSP compression chips allow for storage of months of high-quality video and audio recordings at reduced HDD costs.

Every LINEARIS DVMS has a built-in web server, VisionWeb. It allows viewing of live or recorded images (with audio) as well as control of PTZ cameras over any TCP/IP connection within Internet Explorer web browser - no special software is required. Video quality is handled dynamically by the MPEG4 Adaptive technology, which allows exceptional results even over an extremely limited and fluctuating bandwidth. On constant connections, our MPEG4 Main Profile hardware compression demonstrates all the visual quality and detail LINEARIS and of its new generation DSP based architecture delivers.

• Compact desktop container



- Loophthrough
- Auto-configuration wizard
- Full screen live
- Full screen playback
- Alarm inputs
- Multibrand Network Cameras Support
- Pre-motion recording
- Virtual zoom
- Image print
- Image touch-up
- Image/video export
- Image/video export authentication
- Embedded operating system
- Firmware upgrade via network
- Compatible with existing networks



	LINEARIS LC
Video inputs	Up to 16 universal (Analog / IP)
Loophthrough	Yes
Audio channels	8 mono
Network Spot monitors	Yes via NETTUNO
Local Spot Monitors:	Optional
Audio channels (bi-directional)	1
Alarm inputs (optoisolated)	16
Auxiliary outputs (relay)	16
Operator interface	VGA
Internal storage archive	Up to 800 GB
Raid5 archive with hot swap disks	No
Recording speed	400/480* IPS @ CIF 200/240* IPS @ 2CIF 100/120* IPS @ D1
Resolution	720x576/720x480* D1 720x288/720x240* 2CIF 360x288/360x240* CIF 180x144/180x120* QCIF
IPS per camera	From 1 IPS to 25/30 IPS*
Recording compression algorithms	MPEG4 Main Profile
Transmission compression algorithms	MPEG4 Adaptive
Ethernet ports	Gigabit
USB port	Yes (v2.0)
Serial interface	RS.232
Keyboard / Mouse port	PS/2
Operating system	XP Embedded
Main processor	Intel P4
Power supply	110 / 220 VCA ± 10%
Power consumption	450 W
Operating temperature	5 - 50 °C
Relative humidity	8 - 90% non condensing
Weight	12Kg
Dimensions	430 x 430 x 130 mm

#### HIGH PERFORMANCE AND QUALITY

- No performance degradation with unsynchronised cameras
- Recording speed of 400/480\* images per second at maximum quality
- True Pentaplex Functionality – simultaneous recording, playing, viewing, archiving and transmitting at all times, regardless of image content or system activity
- Powerful networkability – true client-server architecture with full remote control via TCP/IP
- Compression algorithms MPEG4 Main Profile
- Hardware compression for guaranteed performance
- PTZ Control – fully integrated multi-vendor PTZ support with minimum latency
- Multibrand Network Cameras support

#### REAL TIME MOTION DETECTION

- Motion detection – integrated Dynamic Leading Edge motion detection, configurable for each input

#### FULL NETWORKING

- Powerful networkability – true client-server architecture with full remote control via TCP/IP
- Integrated web video/audio server for connections via Internet Explorer
- High quality video transmission on extremely low bandwidth

#### EASY TO USE

- Point-and-click graphic user interface for simple, immediate and precise control
- Visual Search – fast and easy access to all recorded material, simple and effective
- Flexible user management – control access to cameras, functions, bandwidth by user

#### TOP SECURITY

- Embedded hardware architecture
- Embedded operating system
- Integrated firewall for direct Internet connection

CIEFFE are continuously in research and development and therefore reserves the right to alter specifications and prices without notice. For precise information, please contact your CIEFFE representative. Subject to change in design and specifications. Subject to error.



Easy to use "point & click" interface



The search interface displays months of recorded video

#### COMPATIBLE SOFTWARE

- RemoteControl - Full TCP/IP Client
- RemoteView - Simple TCP/IP Client
- VisionWeb - Internet Explorer TCP/IP Client
- SiteManager - Full TCP/IP Multi-server Client
- Cieffe Developer Kit API
- Cieffe VisionPocket

#### HARDWARE OPTIONS

- Internal CD writer
- External USB CD writer
- USB RS422/RS485 interface for dome control

Italy - United Kingdom - Benelux  
New Zealand - Australia - Japan  
USA - Middle East - Singapore

2 year warranty

\* PAL / NTSC

#### CIEFFE s.r.l.

Via Lavoratori Autobianchi, 1  
Edificio 23  
20033 Desio - Milano - ITALY

phone +39 0362 17935

fax +39 0362 1793590

[www.cieffe.com](http://www.cieffe.com)

[info@cieffe.com](mailto:info@cieffe.com)

#### CIEFFE Benelux Bvba

Mechelsesteenweg 244  
B - 1800 Vilvoorde  
Belgium  
Phone +32 (0)2 253 2829  
Fax + 32 (0)2 253 5293

#### CIEFFE (Australia) Pty Ltd

59 - 63 Captain Cook Drive  
Caringbah, NSW 2229  
Australia  
Phone +61 (0) 2 9531 2122  
Fax +61 (0) 2 9531 2126

#### CIEFFE (UK) Ltd

60 Priestley Road  
Surrey Research Park  
Guildford  
Surrey GU2 7YS  
United Kingdom  
Phone +44 (0) 1483 300456  
Fax + 44 (0) 1483 301456

#### CIEFFE (NZ) Ltd

Gnd Floor, 180 Molesworth Street,  
P O Box 2789, Wellington  
New Zealand  
NZ Freephone 0800 PROXIMA  
Phone +64 (0) 4 471 2179  
Fax +64 (0) 4 473 8619

